


Amendment to the Abstract:

The Abstract has been amended. A revised Abstract is attached.

A mechanical resonator is constructed such that it has a vibration body {1}—that performs a mechanical resonant vibration and also has an electrode {2} located in the vicinity of the vibration body {1}—and such that it is shaped into the surface shape of the electrode {2}—when deformed during a resonance mode of the vibration body—{1}, whereby the electrostatic capacitance change per unit vibration displacement amount can be enlarged. In this way, a mechanical resonator can be realized which performs an effective electricity-to-machine or machine-to-electricity conversion. Moreover, this mechanical resonator can be used to realize a small-sized, high-performance filter circuit or switch circuit in a high-density integrated electrical circuit.

Attachment

Respectfully submitted,


Lawrence E. Ashery, Reg. No. 27,424
Attorney for Applicant

LEA/ds


Attachments: Abstract

Dated: June 13, 2005

P.O. Box 980
Valley Forge, PA 19482
(610) 407-0700

EXPRESS MAIL Mailing Label Number: EV 547590493 US
Date of Deposit: June 13, 2005

I hereby certify that this paper and fee are being deposited, under 37 C.F.R. § 1.10 and with sufficient postage, using the "Express Mail Post Office to Addressee" service of the United States Postal Service on the date indicated above and that the deposit is addressed to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.


Kathleen Libby

DAS_I:\MAT\8706US\PREAMEND.DOC

ABSTRACT

A mechanical resonator is constructed such that it has a vibration body that performs a mechanical resonant vibration and also has an electrode located in the vicinity of the vibration body and such that it is shaped into the surface shape of the electrode when deformed during a resonance mode of the vibration body, whereby the electrostatic capacitance change per unit vibration displacement amount can be enlarged. In this way, a mechanical resonator can be realized which performs an effective electricity-to-machine or machine-to-electricity conversion. Moreover, this mechanical resonator can be used to realize a small-sized, high-performance filter circuit or switch circuit in a high-density integrated electrical circuit.